



PART NUMBER	BOLT SIZE	A ±.005	DI	DO	MAXIMUM LENGTH L	(HF)	(HS)	(M)	(P)
CB5908C55()()	.1640	.332	.1670-.1685	.1840-.1850	.750	.041	.045		
CB5908C06()()	.1900	.383	.1930-.1945	.2095-.2105	1.000	.044	.049	.2440	.0358
CB5908C08()()	.2500	.503	.2530-.2545	.2696-.2706	1.000	.058	.063	.3314	.0435
CB5908C10()()	.3125	.595	.3155-.3170	.3321-.3331	1.000	.064	.069	.4046	.0480
CB5908C12()()	.3750	.700	.3780-.3795	.3946-.3956	1.000	.075	.080	.4853	.0537

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	FINISH	SPEC.
C	A-286 CRES	AMS 5525	PASSIVATE	QQ-P-35

EXAMPLE PART NUMBER

CB5908 C 08 B 165

↑ ↑ ↑ ↑
 BASIC PART NUMBER FASTENER DIA IN 32NDS - .2500 INCH
 SURFACE FINISH - POWDER BLAST
 LENGTH L IN THOUSANDTHS - .165 INCH

OPTIONAL SURFACE FINISH

CODE	TREATMENT
-	NONE
B	POWDER BLAST
P	MIL-P-85582 PRIMER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

PANDOR

APPROVALS	DATE
DRAWN DAC	28JAN00
CHECKED DAC	28JAN00
RELEASED CGH	29JAN00
REVISED DAC	28JAN00

TITLE			
SLEEVE, BOLT CLEARANCE, 130° FLUSH HEAD, ADHESIVE BONDED			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	CB5908	1
SCALE	4/1	24FEB99	28JAN00
SHEET 1 OF 1			