



PART NUMBER	THREAD T	A	B	C	D	G	L	M	P	R MAX	±.003 TD	TORX RECESS	MAX INSTALL TORQUE (IN-LBS)
CB9273-3	.190-32	.395	.365	.085	.1900	.438	1.06	.3146	.0785	.020	.1850	T-20	8
CB9273-4	.250-28	.517	.487	.095	.2500	.500	1.56	.4244	.0837	.020	.2450	T-30	25
CB9273-5	.3125-24	.645	.615	.105	.3125	.500	1.56	.5388	.0890	.025	.3070	T-30	50
CB9273-6	.375-24	.772	.742	.110	.3750	.500	1.56	.6531	.0946	.030	.3690	T-40	80

MATERIAL: POLYETHERIMIDE THERMOPLASTIC
 FINISH: AS MOLDED

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
 NEVADA 89706

		APPROVALS	DATE	TITLE			
ANGLES	±1°	DRAWN BSP	29AUG00	BOLT, 100° CSK RIMMED TENSION HEAD, PLASTIC			
.XX	±.03	CHECKED DAC	29AUG00	SIZE	CAGE CODE	DWG. NO.	REV.
.XXX	±.010	RELEASED CGH	29AUG00	A	66530	CB9273	5
.XXXX	±.001	REVISED BSP	29AUG00	SCALE	2/1 29AUG00		SHEET 1 OF 1