



ALL DIMENSIONS PRIOR TO PLATING.

DIMENSION DATA

PART NUMBER	A ±.005 DIA	DI DIA	DO DIA	L MAX
JK5207( )06N( )( )	.380	.2115 .2100	.2275 .2265	1.000

MATERIAL DATA

CODE	MATERIAL	SPEC.	CONDITION	FINISH	SPEC.
C	A-286 CRES	AMS 5525	AS FORMED	PASSIVATE	QQ-P-35
D	A-286 CRES	AMS 5525	ANNEALED	PASSIVATE	QQ-P-35

SURFACE FINISH

CODE	TREATMENT
N	NONE

LUBRICATION DATA

CODE	LUBRICATION	SPEC.
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

EXAMPLE PART NUMBER

JK5207 C 06 N 200 B

LENGTH L IN 16THS OF AN INCH ±.010 (2 DIGITS)  
LENGTH L IN THOUSANDTHS OF AN INCH ±.005 (3 DIGITS)

LUBRICATION - NONE  
 LENGTH L IN THOUSANDTHS - .200  
 SURFACE FINISH - NONE  
 FASTENER DIAMETER IN 32NDS - .1875 INCH  
 MATERIAL - A-286 CRES  
 BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

**GLICK BOND**

CARSON CITY  
NEVADA 89706

SPECIAL

APPROVALS	DATE
DRAWN BSP	31MAR00
CHECKED DAC	31MAR00
RELEASED CGH	3APR00
REVISED BSP	31MAR00

TITLE			
SLEEVE, BOLT CLEARANCE, PROTRUDING HEAD			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5207	C
SCALE	4/1 31MAR00		SHEET 1 OF 1