

DIMENSION DATA (ALL DIMENSIONS PRIOR TO SURFACE FINISH AND LUBRICATION.)

PART NUMBER	FOR BOLT SIZE	A ±0,13	DI DIA	DO DIA	L MAX
JK5701( )04( )( )	4,0	8,5	3,999 3,960	4,499 4,474	19
JK5701( )05( )( )	5,0	10,0	4,999 4,960	5,499 5,474	25
JK5701( )06( )( )	6,0	11,5	5,999 5,960	6,499 6,474	25
JK5701( )08( )( )	8,0	14,5	7,994 7,955	8,494 8,470	25
JK5701( )10( )( )	10,0	17,5	9,994 9,955	10,494 10,470	25
JK5701( )12( )( )	12,0	20,5	11,994 11,955	12,494 12,470	25

LUBRICATION DATA

CODE	LUBRICATION	SPEC.
NONE	NONE	
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

MATERIAL AND FINISH DATA


CODE	MATERIAL	SPEC.	CONDITION	FINISH	SPEC.
C	A-286 CRES	AMS 5525	AS FORMED	PASSIVATE	QQ-P-35
D	A-286 CRES	AMS 5525	ANNEALED	PASSIVATE	QQ-P-35

SURFACE FINISH

CODE	TREATMENT	SPEC.
N	NONE	
AC	ALUMINUM COAT	NAS4006

EXAMPLE PART NUMBER

JK5701 C 08 N 05 L



UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

**GLICK BOND**

CARSON CITY  
NEVADA 89706

DIN65428  
METRIC  
HOLEMOD

APPROVALS	DATE
DRAWN BSP	26AUG02
CHECKED DAC	26AUG02
RELEASED CGH	26AUG02
REVISED BSP	26AUG02

TITLE			
SLEEVE, BOLT FIT, PROTRUDING HEAD, METRIC			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5701	6
SCALE	26AUG02		SHEET 1 OF 1