



DIMENSION DATA (ALL DIMENSIONS PRIOR TO SURFACE FINISH AND LUBRICATION.)

PART NUMBER	FOR BOLT SIZE	A ±0,13	DI DIA	DO DIA	L MAX	(HF)	(HS)
JK5706( )05( )( )	5,0	10,0	4,999 4,960	5,499 5,474	25	2,1	2,22
JK5706( )06( )( )	6,0	12,0	5,999 5,960	6,499 6,474	25	2,6	2,72
JK5706( )08( )( )	8,0	16,0	7,994 7,955	8,494 8,470	25	3,4	3,52
JK5706( )10( )( )	10,0	20,0	9,994 9,955	10,494 10,470	25	4,2	4,32
JK5706( )12( )( )	12,0	24,0	11,994 11,955	12,494 12,470	25	5,0	5,12

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	CONDITION	FINISH	SPEC.
C	A-286 CRES	AMS 5525	AS FORMED	PASSIVATE	QQ-P-35
D	A-286 CRES	AMS 5525	ANNEALED	PASSIVATE	QQ-P-35

LUBRICATION DATA

CODE	LUBRICATION	SPEC.
NONE	NONE	
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

SURFACE FINISH

CODE	TREATMENT	SPEC.
N	NONE	
AC	ALUMINUM COAT	NAS4006

EXAMPLE PART NUMBER

JK5706 C 08 N 08 L

↑ LUBRICATION - CETYL ALCOHOL  
 ↑ LENGTH L IN MM (2 DIGITS) - 8,0 MM  
 ↑ SURFACE FINISH - NONE  
 ↑ FASTENER DIA IN MM - 8,0 MM  
 ↑ MATERIAL - A-286 CRES  
 ↑ BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

**GLICK BOND**

CARSON CITY  
NEVADA 89706

DIN65430  
METRIC  
HOLEMOD

APPROVALS	DATE
DRAWN BSP	26AUG02
CHECKED DAC	26AUG02
RELEASED CGH	26AUG02
REVISED BSP	26AUG02

TITLE			
SLEEVE, BOLT FIT, 100° FLUSH TENSION HEAD, METRIC			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5706	9
SCALE	4/1	26AUG02	SHEET 1 OF 1