



ALL DIMENSIONS PRIOR TO PLATING.

* - LENGTH L IN 1/16 INCH INCREMENTS ±.010 (2 DIGITS)
 LENGTH L IN THOUSANDTHS OF AN INCH ±.005 (3 DIGITS)

DIMENSION DATA

PART NUMBER	FOR BOLT SIZE	A ±.005 DIA	DI DIA	DO DIA	L MAX	HF REF	HS REF
JK5906 () 55 N () ()	#8	.328	.1685 .1670	.1850 .1840	12	.070	.074
JK5906 () 06 N () ()	#10	.380	.1945 .1930	.2105 .2095	16	.080	.084
JK5906 () 08 N () ()	1/4	.505	.2545 .2530	.2706 .2696	16	.108	.112
JK5906 () 10 N () ()	5/16	.631	.3170 .3155	.3331 .3321	16	.135	.139
JK5906 () 12 N () ()	3/8	.758	.3795 .3780	.3956 .3946	16	.162	.166

MATERIAL DATA

CODE	MATERIAL	SPEC.	CONDITION	FINISH	SPEC.
C	A-286 CRES	AMS 5525	AS FORMED	PASSIVATE	QQ-P-35
D	A-286 CRES	AMS 5525	ANNEALED	PASSIVATE	QQ-P-35

SURFACE FINISH

CODE	FINISH	SPEC.
N	NONE	
P	PLATED	SPECIAL
AC	ALUMINUM COAT	NAS 4006

LUBRICATION DATA

CODE	LUBRICATION	SPEC.
NONE	NONE	
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

EXAMPLE PART NUMBER

JK5906 C 06 N 08 L

↑ LUBRICATION - CETYL ALCOHOL
 ↑ LENGTH IN 1/16 INCH INCREMENTS - .500
 ↑ SURFACE FINISH - NONE
 ↑ FASTENER SHANK DIAMETER - .190
 ↑ MATERIAL - A-286 CRES
 ↑ BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.



CARSON CITY
NEVADA 89706

PANDOR
STANDARD

APPROVALS	DATE
DRAWN DAC	28APR00
CHECKED DAC	28APR00
RELEASED CGH	28APR00
REVISED DAC	28APR00

TITLE			
SLEEVE, BOLT CLEARANCE, 100° TENSION HEAD			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5906	L
SCALE	4/1 28APR00		SHEET 1 OF 1