



DIMENSION DATA

CODE	THREAD T	A	B	D MIN	H
3	.1900-32 UNJF-3B	.87	.427 - .437	.700	.200 - .210
4	.2500-28 UNJF-3B	1.00	.552 - .562	.775	.265 - .275

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	FINISH	SPEC.
CR	304 CRES OR A-286 CRES	AMS 5639, 5726, 5731, 5732, 5734, OR 5737	PASSIVATE	QQ-P-35

OPTIONAL PRIMER

CODE	BASEPLATE PRIMER	SPEC.
P	EPOXY PRIMER	MIL-P-85582

EXAMPLE PART NUMBER

CB9312 CR 3-1000 P

↑ BASIC PART NUMBER
 ↑ CR 300 SERIES CRES OR A-286 CRES
 ↑ 3-1000 THREAD SIZE - .1900-32 UNJF-3B
 ↑ 1000 GRIP LENGTH L IN THOUSANDTHS OF AN INCH - 1.000
 ↑ P OPTIONAL PRIMER ON BASEPLATE

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

		APPROVALS	DATE
ANGLES	±1°	DRAWN DAC	17JAN00
.XX	±.03	CHECKED DAC	17JAN00
.XXX	±.010	RELEASED CGH	17JAN00
.XXXX	±.001	REVISED	

TITLE			
BUSHING, THREADED INSERT, BLIND			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	CB9312	0
SCALE	2/1 17JAN00		SHEET 1 OF 1