

LENGTH L DATA (LENGTH L IN SIXTEENTHS OF AN INCH) - SEE TABLE FOR MINIMUM LENGTHS

CODE	8	9	10	11	12	13	14	15	16	17	18	20	22	24	28	32
L	.500	.562	.625	.687	.750	.812	.875	.937	1.000	1.062	1.125	1.250	1.375	1.500	1.750	2.000
D MIN	.218	.295	.472													

STANDOFF MATERIAL AND FINISH DATA

CODE	STANDOFF MATERIAL	SPEC.	FINISH	SPEC.
A	2024 OR 6061	QQ-A-200, QQ-A-225, OR QQ-A-250	NONE	
AA	ALUMINUM		ANODIZE	MIL-A-8625
CR	302, 303, 304 CRES OR A-286 CRES	AMS 5513, 5516, 5625, 5636, 5637, 5638, 5639, 5640, 5641, 5647, 5726, 5731, 5732, 5734, OR 5737 (CHEMISTRY ONLY)	PASSIVATE	QQ-P-35
CRA	A-286 CRES	AMS 5525, 5726, 5731, 5732, 5734, OR 5737 (CHEMISTRY ONLY)	PASSIVATE	QQ-P-35
T	6AL-4V TITANIUM	AMS 4911, 4928, 4965, OR 4967	NONE	

COMPOSITE MATERIAL

CODE	BASEPLATE MATERIAL
C	CARBON/EPOXY, 350°F
G	GLASS/EPOXY, 250°F
E	GLASS/EPOXY, 350°F


THREAD T DATA AND DIMENSIONS

CODE	THREAD SIZE	B DIA	E	MIN L
3	.1900-32 UNF-3B	.31	.28	8
4	.2500-28 UNF-3B	.38	.36	10
5	.3125-24 UNF-3B	.45	.44	11
6	.3750-24 UNF-3B	.53	.50	12

THREAD T  
MS21209 OR NAS1130 INSERT  
INSTALLED PER MS33537. LUBE  
PER MIL-L-46010, TYPE 1.  
THREAD LOCK PER NASM25027.  
ACCOMMODATES MIL-S-8879  
UNJ THREAD SCREW.

EXAMPLE PART NUMBER

CB4201 G 3 AA 12 H 125



OPTIONAL TRIMMED BASE - 1.25  
OPTIONAL INSPECTION HOLE  
STANDOFF LENGTH L - .750  
STANDOFF MATERIAL - ALUMINUM, ANODIZED  
THREAD SIZE T - .1900-32 UNF-3B  
BASEPLATE MATERIAL - GLASS/EPOXY, 250°F  
BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

**GLICK BOND**

CARSON CITY  
NEVADA 89706

APPROVALS		DATE	TITLE			
ANGLES	±1°	DRAWN BSP	STANDOFF, LOCKING THREAD, COMPOSITE BASE, VERY LARGE			
.XX	±.03	CHECKED DAC	SIZE	CAGE CODE	DWG. NO.	REV.
.XXX	±.010	RELEASED CGH	A	66530	CB4201	3
.XXXX	±.001	REVISED BSP	SCALE	1/1 13MAR00		SHEET 1 OF 1