



DISPOSABLE GAGE FIXTURE POSITIONS SLEEVE TO PROVIDE FLUSH MOUNTING OF 130° FLUSH HEAD FASTENER.

DISPOSABLE RETAINER

PART NUMBER	BOLT SIZE	A ±.005	DI	DO	MAXIMUM LENGTH L	(HF)	(HS)	(M)	(P)
CB5948C55()()	.1640	.332	.1670-.1685	.1990-.2000	.750	.041	.051		
CB5948C06()()	.1900	.383	.1930-.1945	.2250-.2260	1.000	.044	.054	.2440	.0358
CB5948C08()()	.2500	.503	.2530-.2545	.2852-.2862	1.000	.058	.068	.3314	.0435
CB5948C10()()	.3125	.595	.3155-.3170	.3477-.3487	1.000	.064	.074	.4046	.0480
CB5948C12()()	.3750	.700	.3780-.3795	.4102-.4112	1.000	.075	.085	.4853	.0537

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	FINISH	SPEC.
C	A-286 CRES	AMS 5525	PASSIVATE	QQ-P-35

EXAMPLE PART NUMBER

CB5948 C 08 B 165

LENGTH L IN THOUSANDTHS - .165 INCH
 SURFACE FINISH - POWDER BLAST
 FASTENER DIA IN 32NDS - .2500 INCH
 MATERIAL - A-286 CRES
 BASIC PART NUMBER

OPTIONAL SURFACE FINISH

CODE	TREATMENT
-	NONE
B	POWDER BLAST
P	MIL-P-85582 PRIMER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

PANDOR

APPROVALS	DATE
DRAWN DAC	28JAN00
CHECKED DAC	28JAN00
RELEASED CGH	29JAN00
REVISED DAC	28JAN00

TITLE			
SLEEVE, BOLT CLEARANCE, 130° FLUSH HEAD, ADHESIVE BONDED			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	CB5948	1
SCALE	4/1	29JUN99	28JAN00
SHEET 1 OF 1			