

DIMENSION DATA (ALL DIMENSIONS PRIOR TO SURFACE FINISH AND LUBRICATION.)

PART NUMBER	FOR BOLT SIZE	A ±0,13	DI DIA	DO DIA	L MAX	(HF)	(HS)
JK5722()05()()	5,0	7,8	4,999 4,960	5,999 5,974	25	1,2	1,42
JK5722()06()()	6,0	9,7	5,999 5,960	6,999 6,974	25	1,5	1,74
JK5722()08()()	8,0	12,7	7,994 7,955	8,994 8,970	25	2,0	2,24
JK5722()10()()	10,0	15,7	9,994 9,955	10,994 10,970	25	2,4	2,64
JK5722()12()()	12,0	19,4	11,994 11,955	12,994 12,970	25	3,0	3,24

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	CONDITION	FINISH	SPEC.
C	A-286 CRES	AMS 5525	AS FORMED	PASSIVATE	QQ-P-35
D	A-286 CRES	AMS 5525	ANNEALED	PASSIVATE	QQ-P-35

LUBRICATION DATA


CODE	LUBRICATION	SPEC.
NONE	NONE	
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

SURFACE FINISH

CODE	TREATMENT	SPEC.
N	NONE	
AC	ALUMINUM COAT	NAS4006

EXAMPLE PART NUMBER

JK5722 C 08 N 08 L



LUBRICATION - CETYL ALCOHOL
 LENGTH L IN MM (2 DIGITS) - 8,0 MM
 SURFACE FINISH - NONE
 FASTENER DIA IN MM - 8,0 MM
 MATERIAL - A-286 CRES
 BASIC PART NUMBER

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

DIN65434
METRIC
HOLEMOD

APPROVALS	DATE
DRAWN BSP	26AUG02
CHECKED DAC	26AUG02
RELEASED CGH	26AUG02
REVISED BSP	26AUG02

TITLE			
SLEEVE, BOLT FIT, 100° FLUSH SHEAR HEAD, METRIC			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5722	6
SCALE	4/1	26AUG02	SHEET 1 OF 1